08/09/2010 11:01 Pag.: 1

_	EGUNTA:	RPTA
	at designated airspace associated with an airport becomes inactive when the control tower at that airport is not in ation?	В
	Class D, which then becomes Class C.	
	Class D, which then becomes Class E. Class B.	
50821 Whi	ch is true regarding flight operations in Class B airspace?	В
	light under VFR is not authorized unless the pilot in command is instrument rated.	
	The pilot must receive an ATC clearance before operating an aircraft in that area. olo student pilot operations are not authorized.	
	ch is true regarding pilot certification requirements for operations in Class B airspace?	В
	he pilot in command must hold at least a private pilot certificate with an instrument rating.	
	he pilot in command must hold at least a private pilot certificate.	
	olo student pilot operations are not authorized.	
	ch is true regarding flight operations in Class B airspace?	А
	The aircraft mus be equipped with an ATC transponder and altitude reporting equipment. The pilot in command must hold at least a private pilot certificate with an instrument rating.	
	The pilot in command must hold at least a student pilot certificate.	
5083 The	minimum flight visibility for VFR flight increases to 5 statute miles beginning at an altitude of	В
	4,500 feet MSL.	
	0,000 feet MSL if above 1,200 feet AGL. 0,000 feet MSL regardless of height above ground.	
	t is the minimum flight visibility and proximity to cloud requirements for VFR flight, at 6,500 feet MSL, in	В
	s C, D, and E airspace?	Б
	mile visibility; clear of clouds.	
	miles visibility; 1,000 feet above and 500 feet below.	
	miles visibility; 1,000 feet above and 1,000 feet below.	
	en operating an airplane for the purpose of landing or takeoff within Class D airspace under special VFR, what imum distance from clouds and what visibility are required?	А
	temain clear of clouds, and the ground visibility must be at least 1 SM.	
	00 feet beneath clouds, and the ground visibility must be at least 1 SM. Temain clear of clouds, and the flight visibility must be at least 1 NM.	
	ome airports located in Class D airspace where ground visibility is not reported, takeoffs and landings under	D
	ial VFR are	В
<b>OPCION A:</b> n	ot authorized.	
	uthorized by ATC if the flight visibility is at least 1 SM.	
	uthorized only if the ground visibility is observed to be at least 3 SM.	
	perate an airplane under SPECIAL VFR (SVFR) within Class D airspace at night, which is required?	C
	The pilot must hold an instrument rating, but the airplane need not be equipped for instrument flight, as ong as the weather will remain at or above SVFR minimums.	
	The Class D airspace must be specifically designated as a night SVFR area.	
OPCION C: 7	he pilot must hold an instrument rating and the airplane must be equipped for instrument flight.	
	cruising altitudes are required to be maintained when flying	В
	t 3,000 feet or more AGL; based on true course.	
	nore than 3,000 feet AGL; based on magnetic course. t 3,000 feet or more above MSL; based on magnetic heading.	
	r an ATC clearance has been obtained, a pilot may not deviate from that clearance, unless the pilot equests an amended clearance.	C

OPCION B: OPCION C:	is operating VFR on top. receives an amended clearance or has an emergency.	
51161 W OPCION A: OPCION B: OPCION C:	When approaching to land at an airport, without an operating control tower, in Class G airspace, the pilot should make all turns to the left, unless otherwise indicated. fly a left-hand traffic pattern at 800 feet AGL. enter and fly a traffic pattern at 800 feet AGL.	A
	Which is true regarding flight operations to or from a satellite airport, without an operating control tower, within the Plass C airspace area? Prior to takeoff, a pilot must establish communication with the ATC controlling facility. Aircraft must be equipped with an ATC transponder and altitude reporting equipment. Prior to landing, a pilot must establish and maintain communication with an ATC facility.	В
	Which is true regarding flight operations to or from a satellite airport, without an operating control tower, within the Plass C airspace area? Prior to entering that airspace, a pilot must establish and maintain communication with the ATC serving facility. Aircraft must be equipped with an ATC transponder. Prior to takeoff, a pilot must establish communication with the ATC controlling facility.	A
51202 W OPCION A: OPCION B: OPCION C:	Which is true regarding flight operations in Class A airspace? Aircraft must be equipped with approved distance measuring equipment (DME). Aircraft must be equipped with an ATC transponder and altitude reporting equipment. May conduct operations under visual flight rules.	В
5272 H OPCION A: OPCION B: OPCION C:	low can you determine if another aircraft is on a collision course with your aircraft? The nose of each aircraft is pointed at the same point in space. The other aircraft will always appear to get larger and closer at a rapid rate. There will be no apparent relative motion between your aircraft and the other aircraft.	С
5504 T OPCION A: OPCION B: OPCION C:	o use VHF/DF facilities for assistance in locating your position, you must have an operative VHF transmitter and receiver. transmitter and receiver, and an operative ADF receiver. transmitter and receiver, and an operative VOR receiver.	А
W OPCION A: OPCION B: OPCION C:	ef. Fig. 54 point 1 Vhat minimum altitude is required to avoid the Livermore Airport (LVK) Class D airspace? 2,503 feet MSL. 2,901 feet MSL. 3,297 feet MSL. sferencial 54.1 en el Manual de Figuras)	В
M OPCION A: OPCION B: OPCION C:	efer. Fig. 52 point 6 fosier Airport is an airport restricted to use by private and recreational pilots. a restricted military stage field within restricted airspace. a nonpublic use airport. eferencial 52. 6 en el Manual de Figuras)	С
T OPCION A: OPCION B: OPCION C:	ef Figure 54 point 6 he Class C airspace at Metropolitan Oakland International (OAK) which extends from the surface upward has a eiling of both 2,100 feet and 3,000 feet MSL. 8,000 feet MSL. 2,100 feet AGL. eferencial 54.6 en el Manual de Figuras)	A

5599 D-f Ein 52		
5588 Ref. Fig. 53		В
GIVEN:		
	Madera Airport (MAE)	
Altitude		
Time Flight visibility		
Flight visionity	1 SM	
	ng Madera Airport for a landing from the north. You	
	FARs; you need 3 miles of visibility under VFR.	
-	nd to below 700 feet AGL to remain clear of Class E airspace and may continue for	
landing.	ACT (D. Handling Altic 1) - Constanting Class Environment 1 - articles of all science of	
<b>OPCION C:</b> may descend to 800 fe (Ver figura referencial 53 en el Manu	eet AGL (Pattern Altitude) after entering Class E airspace and continue to the airport.	
5657 Ref. Fig. 51		С
-	ground control after landing when the aircraft is completely clear of the runway. This is	C
when the aircraft	ground control and maning when the anotate is completely clear of the full way. This is	
<b>OPCION A:</b> passes the red symbol	l shown at the top of the figure.	
<b>OPCION B:</b> is on the dashed-line s	side of the middle symbol.	
-	ide of the middle symbol.	
(Ver figura referencial 51 en el Manu	ual de Figuras)	
5658 Ref. Fig. 51		В
	p would most likely be found	
	ays prior to calling ground control.	
	ere a roadway may be mistaken as a taxiway.	
<b>OPCION C:</b> near the approach end (Ver figura referencial 51 en el Manu		
·		C
56591 Ref. Fig. 51 While clearing an active	runway you are most likely clear of the ILS critical area when you pass which sign?	С
<b>OPCION A:</b> Top red.	runway you are most mery clear of the fills entited area when you puss which sight	
<b>OPCION B:</b> Middle yellow.		
<b>OPCION C:</b> Bottom yellow.		
(Ver figura referencial 51 en el Manu	ual de Figuras)	
56592 Ref. Fig. 51		А
When taxiing up to an ac	tive runway, you are likely to be clear of the ILS critical area when short of which sign?	
<b>OPCION A:</b> Bottom yellow.		
<b>OPCION B:</b> Top red.		
OPCION C: Middle yellow.		
(Ver figura referencial 51 en el Manu		
	does not directly address runway incursion with other aircraft?	А
OPCION A: Top red.		
OPCION B: Middle yellow. OPCION C: Bottom yellow.		
(Ver figura referencial 51 en el Manu	ual de Figuras)	
·		С
5748 Pilots are required to have		C
5748 Pilots are required to hav	-	
<b>OPCION A:</b> anytime an engine is i		
<b>OPCION A:</b> anytime an engine is i <b>OPCION B:</b> anytime the pilots are	erations, both day and night	
OPCION A: anytime an engine is i OPCION B: anytime the pilots are OPCION C: during all types of ope	erations, both day and night	R
OPCION A: anytime an engine is i OPCION B: anytime the pilots are OPCION C: during all types of ope 5749 When in the vicinity of a	-	В

<b>OPCION C:</b>	pass the VOR on the right side of the radial to allow room for aircraft flying in the opposite direction on the same radial.	
5757 A	s hyperventilation progresses, a pilot can experience	С
<b>OPCION A:</b>	decreased breathing rate and depth.	
<b>OPCION B:</b>	heightened awareness and feeling of well being.	
<b>OPCION C:</b>	symptons of suffocation and drowsiness.	
5758 T	o scan properly for traffic, a pilot should	С
<b>OPCION A:</b>	slowly sweep the field of vision from one side to the other at intervals	
<b>OPCION B:</b>	concentrate on any peripheral movement detected.	
<b>OPCION C:</b>	use a series of short, regularly spaced eye movements that bring successive areas of the sky into the central	
	visual field.	
5759 W	/hich is a common sympton of hyperventilation?	А
<b>OPCION A:</b>	Drowsiness.	
<b>OPCION B:</b>	Decreased breathing rate.	
<b>OPCION C:</b>	A sense of well-being.	
5760 W	/hich would most likely result in hyperventilation?	С
<b>OPCION A:</b>	Insufficient oxygen.	
<b>OPCION B:</b>	Excessive carbon monoxide.	
<b>OPCION C:</b>	Insufficient carbon dioxide.	
5761 H	ypoxia is the result of which of these conditions?	В
	Excessive oxygen in the bloodstream.	
<b>OPCION B:</b>	Insufficient oxygen reaching the brain.	
<b>OPCION C:</b>	Excessive carbon dioxide in the bloodstream.	
5762 T	o overcome the symptons of hyperventilation, a pilot should	В
<b>OPCION A:</b>	swallow or yawn.	
<b>OPCION B:</b>	slow the breathing rate.	
<b>OPCION C:</b>	increase the breathing rate.	
5763 W	/hich is true regarding the presence of alcohol within the human body?	С
<b>OPCION A:</b>	A small amount of alcohol increases vision acuity.	
<b>OPCION B:</b>	An increase in altitude decreases the adverse effect of alcohol.	
<b>OPCION C:</b>	Judgement and decision-making abilities can be adversely affected by even small amounts of alcohol.	
5764 H	ypoxia susceptibility due to inhalation of carbon monoxide increases as	В
<b>OPCION A:</b>	humidity decreases.	
<b>OPCION B:</b>	altitude increases.	
<b>OPCION C:</b>	oxygen demand increases.	
5765 T	o best overcome the effects of spatial disorientation, a pilot should	С
<b>OPCION A:</b>	rely on body sensations.	
<b>OPCION B:</b>	increase the breathing rate.	
<b>OPCION C:</b>	rely on aircraft instrument indications.	
5768 If	necessary to take off from a slushy runway, the freezing of landing gear mechanisms can be minimized by	A
<b>OPCION A:</b>	recycling the gear.	
<b>OPCION B:</b>	delaying gear retraction.	
<b>OPCION C:</b>	increasing the airspeed to Vle before retraction.	
5941 R	isk management, as part of the Aeronautical Decision Making (ADM) process, relies on which features to reduce	С
	e risks associated with each flight?	
<b>OPCION A:</b>	The mental process of analyzing all information in a particular situation and making a timely decision on	
ODCION P	what action to take.	
<b>OPCION B:</b>	Application of stress management and risk element procedures.	

08/09/2010 11:01 Pag.: 5

OPCION C:	Situational awareness, problem recognition, and good judgment.	
5942 A	Aeronautical Decision Making (ADM) is a	А
OPCION A:	systematic approach to the mental process used by pilots to consistently determine the best course of action for a given set of circumstances.	
OPCION B: OPCION C:	decision making process which relies on good judgement to reduce risks associated with each flight. mental process of analyzing all information in a particular situation and making a timely decision on what action to take.	
	The Aeronautical Decision Making (ADM) process identifies the steps involved in good decision making. One of hese steps includes a pilot making a rational evaluation of the required actions. developing the "right stuff" attitude. identifying personal attitudes hazardous to safe flight.	С
5944 E OPCION A: OPCION B: OPCION C:	Examples of classic behavioral traps that experienced pilots may fall into are: trying to assume additional responsibilities and assert PIC authority. promote situational awareness and then necessary changes in behavior. complete a flight as planned, please passengers, meet schedules, and demonstrate the "right stuff".	С
5945 T OPCION A: OPCION B: OPCION C:	The basic drive for a pilot to demonstrate the "right stuff" can have an adverse effect on safety, by a total disregard for any alternative course of action. generating tendencies that lead to practices that are dangerous, often illegal, and may lead to a mishap. imposing a realistic assessment of piloting skills under stressful conditions.	В
	Aost pilots have fallen prey to dangerous tendencies or behavior problems at some time. Some of these dangerous endencies or behavior patterns which must be identified and eliminated include: Deficiencies in instrument skills and knowledge of aircraft systems or limitations. Performance deficiencies from human factors such as, fatigue, illness or emotional problems. Peer pressure, get-there-itis, loss of positional or situation awareness, and operating without adequate fuel reserves.	С
5947 A OPCION A: OPCION B: OPCION C:	An early part of the Aeronautical Decision Making (ADM) process involves taking a self-assessment hazardous attitude inventory test. understanding the drive to have the "right stuff". obtaining proper flight instruction and experience during training.	А
5948 F OPCION A: OPCION B: OPCION C:	Iazardous attitudes which contribute to poor pilot judgment can be effectively counteracted by early recognition of hazardous thoughts. taking meaningful steps to be more assertive with attitudes. redirecting that hazardous attitude so that appropriate action can be taken.	С
5949 V OPCION A: OPCION B: OPCION C:	What are some of the hazardous attitudes dealt with in Aeronautical Decision Making (ADM)? Antiauthority (don't tell me), impulsivity (do something quickly without thinking), macho (I can do it). Risk management, stress management, and risk elements. Poor decision making, situational awareness, and judgment.	А
	When a pilot recognizes a hazardous thought, he or she then should correct it by stating the correspondig antidote. Which of the following is the antidote for MACHO? Follow the rules. They are usually right. Not so fast. Think first. Taking chances is foolish.	С
5951 V OPCION A: OPCION B: OPCION C:	Vhat is the first step in neutralizing a hazardous attitude in the ADM process? Recognition of invulnerability in the situation. Dealing with improper judgment. Recognition of hazardous thoughts.	С
5952 V OPCION A:	Vhat should a pilot do when recognizing a thought as hazardous? Avoid developing this hazardous thought.	С

ODCION D. Develop this beneficing the solution of follow threads with modified action	
<ul><li>OPCION B: Develop this hazardous thought and follow through with modified action.</li><li>OPCION C: Label that thought as hazardous, then correct that thought by stating the corresponding learned antidote.</li></ul>	
5953 To help manage cockpit stress, pilots must	В
<b>OPCION A:</b> be aware of life stress situations that are similar to those in flying.	_
<b>OPCION B:</b> condition themselves to relax and think rationally when stress appears.	
<b>OPCION C:</b> avoid situations that will improve their abilities to handle cockpit responsibilities.	
5954 What does good cockpit stress management begin with?	С
<b>OPCION A:</b> Knowing what causes stress.	
<b>OPCION B:</b> Eliminating life and cockpit stress issues.	
OPCION C: Good life stress management.	
5955 The passengers for a charter flight have arrived almost an hour late for a flight that requires a reservation. Which of the following alternatives best illustrates the ANTIAUTHORITY reaction?	А
<b>OPCION A:</b> Those reservation rules do not apply to this flight.	
OPCION B: If the pilot hurries, he or she may still make it on time.	
OPCION C: The pilot can't help it that the passengers are late.	
5956 While conducting an operational check of the cabin pressurization system, the pilot discovers that the rate control	A
feature is inoperative. He knows that he can manually control the cabin pressure, so he elects to disregard the	
discrepancy. Which of the following alternatives best illustrates the INVULNERABILITY reaction?	
<b>OPCION A:</b> What is the worst that could happen.	
<b>OPCION B:</b> He can handle a little problem like this.	
<b>OPCION C:</b> It's too late to fix it now.	
5957 The pilot and passengers are anxious to get to their destination for a business presentation. Level IV thunderstorms	А
are reported to be in a line across their intended route of flight. Which of the following alternatives best illustrates	
the IMPULSIVITY reaction?	
<b>OPCION A:</b> They want to hurry and get going, before things get worse.	
<b>OPCION B:</b> A thunderstorm won't stop them.	
<b>OPCION C:</b> They can't change the weather, so they might as well go.	
5958 While on an IFR flight, a pilot emerges from a cloud to find himself within 300 feet of a helicopter. Which of the	В
following alternatives best illustrates the MACHO reaction?	
<b>OPCION A:</b> He is not too concerned; everything will be alright.	
OPCION B: He flies a little closer, just to show him.	
OPCION C: He quickly turns away and dives, to avoid collision.	
5959 When a pilot recognizes a hazardous thought, he or she then should correct it by applying the correspondig antidote.	C
Which of the following is the antidote for ANTIAUTHORITY/ DON'T TELL ME hazardous attitude?	
OPCION A: Not so fast. Think first.	
<b>OPCION B:</b> It won't happen to me. It could happen to me. <b>OPCION C:</b> Don't tell me. Follow the rules. They are usually right.	
5960 A pilot and friends are going to fly an out-of-town football game. When the passengers arrive, the pilot determines that they will be over the maximum gross weight for takeoff with the existing fuel load. Which of the following	А
alternatives best illustrates the RESIGNATION reaction?	
<b>OPCION A:</b> Well, nobody told him about the extra weight.	
<b>OPCION B:</b> Weight and balance is a formality forced on pilots by the DGAC.	
<b>OPCION C:</b> He can't wait around to de-fuel, they have to get there on time.	
5961 Which of the following is the final step of the Decide Model for effective risk management and Aeronautical	В
Decision Making?	
OPCION A: Estimate.	
OPCION B: Evaluate.	
OPCION C: Eliminate.	
	А
5962 Which of the following is the first step of the Decide Model for effective risk management and Aeronautical	

<b>OPCION A:</b>	Detect.	
<b>OPCION B:</b>	Identify.	
<b>OPCION C:</b>	Evaluate.	
5963 T	he Decide Model is comprised of a 6-step process to provide a pilot a logical way of approaching Aeronautical	А
D	ecision Making. These steps are:	
<b>OPCION A:</b>	Detect, estimate, choose, identify, do, and evaluate.	
<b>OPCION B:</b>	Determine, evaluate, choose, identify, do, and eliminate.	
<b>OPCION C:</b>	Determine, eliminate, choose, identify, detect, and evaluate.	